

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
1 November 2001 (01.11.2001)

PCT


(10) International Publication Number
WO 01/82299 A1

- (51) International Patent Classification⁷: **G11B 11/105** (74) Agent: **SCHRIJNEMAEKERS, Hubert, J., M.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: **PCT/EP01/03939**
- (22) International Filing Date: **6 April 2001 (06.04.2001)** (81) Designated States (*national*): **BR, CN, CZ, HU, JP, KR, PL, RU, SG.**
- (25) Filing Language: **English**
- (26) Publication Language: **English** (84) Designated States (*regional*): **European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).**
- (30) Priority Data:
00201412.4 19 April 2000 (19.04.2000) EP Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]**; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors: **VAN KESTEREN, Hans, W.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **PENNING, Frank, C.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **MAGNETIC HEAD HAVING A MAGNETIC COIL**



(57) Abstract: A magnetic head suitable for use in a magneto-optical apparatus. The magnetic head has a flat electromagnetic coil (1) with a central opening (3). The coil has parallel coil layers (5a, 5b), each of the coil layers having a turn (5A, 5B) arranged around the central opening. At least one of the coil layers has turns of which the turns closer to the central opening have smaller widths (*w*) than the turns further away from the central opening. At least one of the coil layers has an outermost turn (5B_o) situated closer to the central opening than the outermost turn (5A_o) of one of the other coil layers. The defined coil structure has a limited capacitance while the power dissipation is also limited.



Magnetic head having a magnetic coil

The invention relates to magnetic head for use in a magneto-optical device, which magnetic head includes an at least substantially flat magnetic coil having a central opening, which coil has coil layers which extend at least substantially parallel to each other, each of the coil layers having at least one electrically conductive turn which extends around
5 the central opening.

Such a magnetic head is known from WO-A 98/48418. The known magnetic head includes a flat magnetic coil having two parallel substantially equiform coil sections, each coil section comprising a plurality of turns formed by means of a thin-film technology. The magnetic coil extends in a magnetic yoke which, with the coil, defines a central
10 passageway for an optical beam. The known magnetic head is intended for use in a magneto-optical (MO) system for the storage of data in a magneto-optical medium. During the recording or read-out of data the magnetic head is situated at a short distance from the magneto-optical medium. The magneto-optical system comprises said magnetic head, a laser source and optical elements, which include a focusing lens, enabling a laser beam to be
15 routed to a recording layer via the central passageway. During the storage of data a laser beam is utilized for reducing the coercivity of the recording layer of the magneto-optical medium in that selected spots are heated to approximately the Curie temperature of the recording layer. Meanwhile, the magnetic coil is activated to generate a time-varying magnetic field traversing the recording layer in order to define a pattern of magnetic
20 domains. During the read-out of stored information the MO medium is scanned with a laser beam, use being made of the magneto-optical Kerr effect, which is known per se.

During the magneto-optical storage of information the minimum width of the stored data bits is dictated by the diffraction limit, i.e. the numerical aperture (NA) of the focusing lens used and the wavelength of the laser beam. A reduction of said width is
25 generally based on shorter-wavelength lasers and higher-NA optical focusing systems. During magneto-optical recording the minimum bit length can be reduced to below the optical diffraction limit by using Laser Pulsed Magnetic Field Modulation. In this process the bit transitions are determined by the speed of reversal of the magnetic field and the temperature gradient induced by switching of the laser source. In order to obtain small bit

lengths and high data rates magnetic coils are required which meet specific requirements such as a low self-inductance, a low capacitance and a low resistance. These requirements cannot be met by means of conventionally wound coils. Therefore, use is now made of coils manufactured by means of a multi-layer technique, particularly a thin-film technique.

5 A magnetic coil suitable for high data rate magneto-optical recording should have a good high-frequency behavior. This means that such a coil should have a satisfactorily low self-inductance, a low capacitance and a low resistance, while the power dissipation should be of an acceptable level. Thus, it is true that an increase of the number of turns of a given coil configuration may lead to a reduction of the current required to generate a certain
10 magnetic field, since the power dissipation is proportional to the square of the current and is only proportional to the resistance, but an increase of the number of turns also leads to an increase of the self-inductance and thereby limits the data rate.

 The coil configuration used in the known magnetic head does not provide a solution to the problem outlined above.

15 It is an object of the invention to provide a magnetic head which is suitable for use in a magneto-optical device for information storage at a high speed, for example 100 Mbit/s, and which for this reason includes a magnetic coil which can be used at high switching frequencies and which has an acceptably low power dissipation for its envisaged use.

20 This object is achieved with the magnetic head according to the invention, which magnetic head includes an at least substantially flat magnetic coil having a central opening, which coil has coil layers which extend at least substantially parallel to each other, each of the coil layers having at least one electrically conductive turn which extends around the central opening, wherein at least one of the coil layers has turns, of which the turns
25 situated nearer the central opening have smaller widths than the turns situated farther away from the central opening, at least one of the coil layers having an outermost turn situated nearer the central opening than the outermost turn of one of the other coil layers.

 The central opening of the magnetic coil can serve as a passage for a laser beam. The central opening, which is defined by inner turns, may actually be an opening or it may be a
30 transparent central area formed by a material that differs from the coil material, particularly a transparent material, such as Al_2O_3 , SiO_2 , Si_3N_4 . The turns may be formed from metals such as Cu, Au, Al. In the magnetic head in accordance with the invention the magnetic coil has a turns density which decreases outwardly from the central opening, which has a favorable effect on the power dissipation of the coil, while the coil layers have mutually different

dimensions, which keeps the capacitance within bounds. For an adequate magneto-optical recording it is important that the magnetic coil is capable of generating a magnetic field of the order of 200 Oe (16 kA/m) in and near the central opening. Since the turns which are situated nearer the central opening are most effective in generating the magnetic field, they provide a significant contribution to the generation of the magnetic field in and in the vicinity of the central opening. As a result of a low self-inductance and a low capacitance the magnetic head in accordance with the invention exhibits a good high-frequency behavior. This is corroborated by experiments. The magnetic head is suitable for use in MO devices for information storage with a very high density, for example 100 Gbit/in². Another important effect of the measures in accordance with the invention is that a comparatively large central opening can be used. A comparatively large central opening may be desired if the magnetic head is used in a slider of a magneto-optical device, in which an optical system has been provided and in which a part of the optical system has a mechanically non-rigid connection to the slider. Furthermore, a large central opening may be desirable for the purpose of tracking, for which the position of a laser beam relative to the central opening is varied. The magnetic head in accordance with the invention can be used not only for information recording but also for information reading.

In order to limit the thickness of the magnetic coil the number of coil layers in the magnetic head will be limited to 2 or 3.

Claim 2 defines a practical embodiment of the magnetic head in accordance with the invention.

An embodiment of the magnetic head in accordance with the invention is characterized in that the decrease of the widths of the turns towards the central opening varies uniformly. In the case of a circular magnetic coil the distance between the turns of a coil layer is preferably maintained constant for technological reasons and is preferably minimized in order to guarantee a high efficiency of the coil. Here, efficiency is to be understood to mean the strength of the magnetic field generated at a given power. The width of a turn is preferably proportional to the n-th power of the distance to the central axis of the magnetic coil, which axis extends through the central opening, where

$0.7 \leq n \leq 2$.

An embodiment of the magnetic head in accordance with the invention is characterized in that the one outermost turn is situated substantially nearer the central opening than the other outermost turn. The number of turns of the one coil layer can be substantially smaller than the number of turns in the other coil layer, for example half this

number. It has been found that this enables significant reductions in capacitance and power dissipation to be achieved.

An embodiment of the magnetic head in accordance with the invention is characterized in that the coil layers are thin-film layers. The magnetic coil is consequently a
5 coil manufactured by means of a thin-film technique. The applied technique may be a technique which is known per se. It has been found that the high-frequency behavior can be further improved if at least two coil layers, preferably all the coil layers, are arranged on a flat base because this yields a further reduction of the parasitic capacitance and conductance. Claim 6 defines an embodiment of the magnetic head in accordance with the invention which
10 relates to this aspect. The invention also relates to a method of manufacturing the magnetic head in accordance with the invention. The method in accordance with the invention is defined in claim 7. The measure defined in claim 7 means that the production process includes one or more planarizing operations. This means, for example, that after the deposition of an insulating layer a mechano-chemical polishing step is carried out.
15 Alternatively, a spin-on-glass planarization may be used. The methods mentioned are both known per se.

The invention further relates to a slider for use in a magneto-optical device and provided with the magnetic head in accordance with the invention, notably as defined in any one of the claims 1 through 6.

20 The slider in conjunction with a magneto-optical medium ensures that in operation an air film is formed between the magnetic head and the medium, the magnetic head floating at a substantially constant distance from the magneto-optical medium, which can be achieved in a manner known per se.

An embodiment of the slider in accordance with the invention has a slider
25 body with which the magnetic coil is integrated.

The invention further relates to a magneto-optical device including the magnetic head in accordance with the invention, particularly as defined in any one of the claims 1 through 6, or including the slider in accordance with the invention, particularly as defined in claim 8 or 9. The magneto-optical device in accordance with the invention is
30 suitable for magneto-optically recording information in a magneto-optical medium in a manner known per se. The device is also suitable for reading information.

With reference to the claims, it is to be noted that various combinations of characteristic features and measures as defined in the claims are possible.

The invention will now be described in more detail, by way of example, with reference to the drawings, in which:

Fig. 1 is a diagrammatic plan view which shows an embodiment of the magnetic head in accordance with the invention,

5 Fig. 2 shows the embodiment of the magnetic head in a sectional view taken on the line II-II in Fig. 2,

Fig. 3 is a graph which represents the impedance as a function of the frequency for the embodiment of the magnetic head,

10 Fig. 4 is a graph which represents the field strength of the magnetic field as a function of the distance from the central axis of the embodiment of the magnetic head,

Fig. 5 is a diagrammatic side view which shows an embodiment of the slider in accordance with the invention,

Fig. 6 is a diagrammatic underneath view which shows the embodiment of the slider in accordance with the invention,

15 Fig. 7 diagrammatically shows a first application of the slider in accordance with the invention,

Fig. 8 diagrammatically shows a second application of the slider in accordance with the invention,

20 Fig. 9 diagrammatically shows an embodiment of the magneto-optical device in accordance with the invention.

The embodiment of the magnetic head in accordance with the invention shown in Figs. 1 and 2 is suitable for use in a magneto-optical device. The magnetic head includes a flat round electromagnetic coil 1, briefly referred to as the magnetic coil 1 and having a
25 central opening 3 with a central coil axis 3a. The magnetic coil 1 in the present example has two coil layers 5a and 5b, which extend parallel to one another and which are separated from one another by an insulating layer 5c of, for example, SiO_2 . The coil layer 5a in the present example has seven turns 5A made of Cu, including an outermost turn $5A_o$ and an innermost turn $5A_i$ situated near the central opening 3. The coil layer 5b in the present example has four
30 turns 5B, also made of Cu, including an outermost turn $5B_o$ and an innermost turn $5B_i$ situated near the central opening 3. The central opening 3 is filled with a transparent material such as SiO_2 . Each set of turns 5A and 5B has a connecting surface 7a and 7b, respectively, the two sets being electrically interconnected by an interconnection 7C.

In the present example the turns in each of the coil layers 5a and 5b have a spiral shape. Of the set of turns 5A and 5B the turns situated nearer the central opening 3 have a smaller width w than the turns situated farther away from the central opening 3. Viewed from the turns 5A_i and 5B_i the width w gradually increases towards the turns 5A_o and 5B_o. In the present example the distance d between the turns in each of the coil layers 5a and 5b is constant. The outermost turn 5B_o has a substantially smaller diameter than the outermost turn 5A_o. The present magnetic coil can be manufactured by means of a thin-film technique which is known per se, in which case it is preferred to carry out a planarizing operation, for example a mechano-chemical polishing operation, before a coil layer is made, in order to obtain a flat base for the relevant coil layer. The thin-film layers may be deposited on a substrate, for example formed by a slider body of a slider.

The graphical representation in Fig. 3 shows the measured impedance Z of the embodiment shown in Figs. 1 and 2 as a function of the frequency f . Therein, $\text{Re}Z$ is the real impedance, $\text{Im}Z$ is the imaginary impedance and $\omega = 2\pi f$.

The graphical representation in Fig. 4 shows the calculated magnetic field strength H_z of a model which closely resembles the embodiment shown in Figs. 1 and 2 as a function of the radius r of the magnetic coil, determined at a height h of 13 μm , reckoned from the side of the coil layer 5a which is remote from the coil layer 5b (see also Figs. 1 and 2). The diameter of the central opening is 90 μm , the diameter of the magnetic coil is 306 μm , and the overall height of the magnetic coil is 9 μm .

The slider in accordance with the invention shown in Figs. 5 and 6 is suitable for use in a magneto-optical device and has a transparent slider body 11, made of glass in the present example, in which an embodiment of the magnetic head in accordance with the invention is integrated. The magnetic coil provided therein is referenced 13. The slider has a structured surface 11a intended for cooperation with an information medium, particularly an MO medium. A focusing lens 15 is mounted on a side 11b which is remote from the surface 11a, in the present example on the slider body 11.

The application shown in Fig. 7 includes a slider of the type as shown in Figs. 5 and 6. The slider, referenced 21 here, cooperates with an optical system which, in addition to the focusing lens 15, includes an objective lens 25. During scanning an MO medium 27 having a recording layer 27a is moved relative to the slider 21, the slider 21 floating at a small distance from the MO medium. A laser beam 29 is then focused to a spot 29a in the recording layer 27a.

Fig. 8 shows another application using a slider 31 of a type as shown in Figs. 5 and 6 but without a focusing lens. In this application the slider 31 also floats above an MO medium 37 but the laser beam 39 required for scanning traverses a transparent substrate 37b of the medium 37 before it reaches an MO layer 37a. For this purpose, the medium 37 is
5 interposed between the slider 31 and an objective lens 35 of an optical system.

The embodiment of the device in accordance with the invention shown in Fig. 9 has a frame 51 which rotatably supports a spindle 53 for an MO disc 55 and which has two magnetic yokes of a slide drive secured to it. The slide drive further includes two drive coils 59a which cooperate with the yokes 57. The drive coils 59a form parts of a slide 59 capable
10 of performing radial translational movements with respect to the spindle 53. The slide 59 has a spring suspension 61, which carries an embodiment 63 of the slider in accordance with the invention. In the present example the slider 63 is of a type as shown in Fig. 5.



It is to be noted that the invention is not limited to the examples shown herein. Thus, the magnetic coil may have more than two coil layers. Moreover, one of the coil layers
15 may include only one turn. Furthermore, it is possible to use a magnetic head in accordance with the invention secured to or mounted on the slider, instead of a magnetic head integrated in the slider.

CLAIMS:

1. A magnetic head for use in a magneto-optical device, which magnetic head includes an at least substantially flat magnetic coil having a central opening, which coil has coil layers which extend at least substantially parallel to each other, each of the coil layers having at least one electrically conductive turn which extends around the central opening,
5 wherein at least one of the coil layers has turns, of which the turns situated nearer the central opening have smaller widths than the turns situated farther away from the central opening, at least one of the coil layers having an outermost turn situated nearer the central opening than the outermost turn of one of the other coil layers.
- 10 2. A magnetic head as claimed in claim 1, wherein at least two coil layers have turns, of which turns the turns situated nearer the central opening have smaller widths than the turns situated farther away from the central opening.
3. A magnetic head as claimed in claim 1 or 2, wherein the decrease of the
15 widths of the turns towards the central opening varies uniformly.
4. A magnetic head as claimed in claim 1, wherein the one outermost turn is situated substantially nearer the central opening than the other outermost turn.
- 20 5. A magnetic head as claimed in claim 1, wherein the coil layers are thin-film layers.
6. A magnetic head as claimed in claim 5, wherein at least two of the coil layers are arranged on a flat base.
- 25 7. A method of manufacturing the magnetic head as claimed in any one of the preceding Claims, wherein planarizing is effected after the provision of a first coil layer but before the provision of a second collector layer.

8. A slider for use in a magneto-optical device and including the magnetic head as claimed in any one of the preceding Claims.
9. A slider as claimed in claim 8, having a slider body with which the magnetic
5 head is integrated.
10. A magneto-optical device including the magnetic head as claimed in any one of the claims 1 through 6.
- 10 11. A magneto-optical device including the slider as claimed in claim 8 or 9.

1/5



2/5




FIG. 3

3/5




FIG. 4

4/5




FIG. 5




FIG. 6




FIG. 7




FIG. 8

5/5




FIG. 9

INTERNATIONAL SEARCH REPORT

International Application No

EP/EP 01/03939

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B11/105

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 98 48418 A (QUINTA CORP ;WANG YUGANG (US); MCDANIEL TERRY (US); READ RITE CORP) 29 October 1998 (1998-10-29) cited in the application page 25, line 7 -page 32, line 27; figure 29	1-11
Y	WO 99 56277 A (BERG JOHN ;KINDLER DAVID (US); LI HONG (US); TERASTOR CORP (US); O) 4 November 1999 (1999-11-04) page 14, line 7 -page 17, line 23; figures 8,9	1-11
Y	US 5 936 814 A (ASH KENNETH P ET AL) 10 August 1999 (1999-08-10) column 3, line 23 -column 5, line 13	7



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

19 September 2001

Date of mailing of the international search report

26/09/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nanos, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/03939

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 492 888 A (SONY CORP AMERICA) 1 July 1992 (1992-07-01) the whole document ---	1-11
A	EP 0 341 778 A (PHILIPS NV) 15 November 1989 (1989-11-15) the whole document ---	1
A	WO 99 24970 A (READ RITE CORP) 20 May 1999 (1999-05-20) the whole document -----	1-11

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/03939

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9848418	A	29-10-1998	US 5903525 A US 5886959 A WO 9848418 A1	11-05-1999 23-03-1999 29-10-1998
WO 9956277	A	04-11-1999	AU 3765699 A WO 9956277 A1	16-11-1999 04-11-1999
US 5936814	A	10-08-1999	NONE	
EP 0492888	A	01-07-1992	US 5402293 A DE 69132614 D1 EP 0492888 A2 EP 0742557 A2 JP 4360049 A	28-03-1995 21-06-2001 01-07-1992 13-11-1996 14-12-1992
EP 0341778	A	15-11-1989	AT 114858 T AU 639412 B2 AU 3408889 A BR 8902141 A CA 1321644 A1 CN 1037791 A DE 68919528 D1 DE 68919528 T2 EP 0341778 A2 ES 2065368 T3 HK 45696 A JP 1319149 A JP 2803841 B2 KR 204689 B1 US 5014254 A	15-12-1994 29-07-1993 09-11-1989 02-01-1990 24-08-1993 06-12-1989 12-01-1995 14-06-1995 15-11-1989 16-02-1995 22-03-1996 25-12-1989 24-09-1998 15-06-1999 07-05-1991
WO 9924970	A	20-05-1999	US 5978319 A US 6130863 A WO 9924970 A2	02-11-1999 10-10-2000 20-05-1999